



EM-1200 / EM-1200L


Features

e-lock-1200 Series electromagnetic locks offer cost effective solution with easy installation & suitable for variety of application . It has no moving parts thus keeping maintenance to a minimum. All types of brackets are available to ease installation for both in-swing & out-swing doors.

Specification

- 1200lbs holding force
- Dual voltage 12 & 24 Vdc
- Current drawn 500mA / 250mA
- MOV surge protection
- Fail-Safe type
- Unmonitored Model (e-lock-1200) & Monitored Model (e-lock-1200L)
- Push-off button on armature for instant release
- Dimension : -
Magnet : 265(L) X 66(W) X 40(D) mm
Armature Plate : 185(L) X 60(W) X 17(D) mm


User Guide



Optional Brackets


EL-BKL (L Bracket)

- Adjustable "L" bracket for outward door when the header is narrow.
- Available for elock-300, 600 & 1200 Series



EL-BKZ (ZL Bracket)


- Adjustable "ZL" bracket for inward door application.
- Available for elock-300, 600 & 1200 Series



Mounting Diagram


Standard Mounting:

- With Filler Plate attached on top of EM Lock.



L Bracket Mounting :

- Mounting with "Adjustable L Bracket" when Door frame is narrow.
- Mounting Procedure :-
Remove the original "Filler Plate" attached to EM Lock, replaced with "Adjustable L Bracket" set.



ZL Bracket mounting :

- Mounting with " ZL Bracket " for In-swung door application.
- Mounting Procedure :-
Remove the original "Filler Plate" attached to EM Lock, replaced with "Adjustable ZL Bracket" set.

